

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

**IN THE CLAIMS**

1. (currently amended) A molded closure comprising:

a cylindrical side wall having ~~at least one cylindrical wall portion, said cylindrical wall portion~~ having a first inner wall on which an auxiliary thread is disposed, said auxiliary thread being inwardly directed;

said side wall also having at least one principal thread being inwardly directed thereon;  
and,

said auxiliary thread being disposed at a first end of said side wall and said principal thread being disposed toward an opposed second end of said side wall;[.]

said auxiliary thread having a first depth and said principal thread having a second depth, said second depth being at least about twice said first depth.

2. (original) The molded closure of claim 1, wherein said auxiliary thread is helical.
3. (original) The molded closure of claim 1, wherein said side wall includes at least one tier.
4. (original) The molded closure of claim 3, wherein said side wall includes a distal tier and a proximal tier, said distal tier including said first inner wall of said cylindrical wall portion and said proximal tier including a second inner wall, said auxiliary thread being disposed on said first inner wall and said principal thread being disposed on said second inner wall.
-

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

5. (original) The molded closure of claim 1, wherein said auxiliary thread includes a first pitch and said principal thread includes a second pitch, said first pitch being unequal to said second pitch.

6. (original) The molded closure of claim 1, wherein said auxiliary thread is incongruent with said principal thread.

7. (currently amended) A molded closure comprising:

a side wall having ~~at least one cylindrical wall portion, said cylindrical wall portion~~  
having a first inner wall on which an auxiliary thread is disposed, said auxiliary thread being inwardly directed;

said side wall also having at least one principal thread, said principal thread being inwardly directed;

said auxiliary thread being disposed toward a first end of said side wall and said principal thread being disposed toward a second end of said side wall; ~~and,~~

said auxiliary thread being incongruent to said principal thread;[[.]]

said auxiliary thread having a first depth and said principal thread having a second depth,  
said first depth being less than about one-half said second depth.

---

8. (original) The molded closure of claim 7, wherein said auxiliary thread is helical.

9. (original) The molded closure of claim 7, wherein said side wall includes at least one tier.

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

10. (currently amended) The molded closure of claim 9, wherein said side wall includes a first tier and a second tier, said first tier including said first inner wall of said ~~cylindrical~~ side wall portion and said second tier including a second inner wall, said auxiliary thread being disposed on said first inner wall and said principal thread being disposed on said second inner wall.

11. (original) The molded closure of claim 7, wherein said auxiliary thread includes a first pitch and said principal thread includes a second pitch, said first pitch being unequal to said second pitch.

12. (currently amended) A molded closure comprising:

a cylindrical side wall having ~~at least one cylindrical wall portion, said cylindrical wall portion having~~ an auxiliary inwardly directed thread disposed thereon, said auxiliary inwardly directed thread being helical;

said side wall also having at least one principal inwardly directed thread; and,

said auxiliary inwardly directed thread being disposed toward a first end of said side wall and said principal inwardly directed thread being disposed toward a second end of said side wall, said auxiliary inwardly directed thread having a first depth, said principal inwardly directed thread having a second depth, wherein said second depth is greater than said first depth by a factor of at least two.

---

13. (original) The molded closure of claim 12, wherein said side wall includes at least one tier.

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

14. (original) The molded closure of claim 13, wherein said side wall has a first tier and a second tier, said first tier including a first inner wall and said second tier including a second inner wall, said auxiliary inwardly directed thread being disposed on said first inner wall and said principal inwardly directed thread being disposed on said second inner wall.

15. (original) The molded closure of claim 14, wherein said first depth is less than one-half the length of said second depth.

16. (original) The molded closure of claim 12, wherein said auxiliary inwardly directed thread includes a first pitch and said principal inwardly directed thread includes a second pitch, said first pitch being unequal to said second pitch.

17. (currently amended) A molded closure comprising:

a cylindrical side wall having at least one ~~cylindrical wall portion~~, said ~~cylindrical wall portion~~ having a first inner wall on which an auxiliary thread is disposed, said auxiliary thread being inwardly directed;

said side wall also having at least one principal thread, said principal thread being inwardly directed;

said auxiliary thread being disposed toward a first end of said side wall and said principal thread being disposed toward a second end of said side wall; and,

---

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francols

said side wall having a first diameter intersecting a portion of said auxiliary thread and said side wall having a second diameter intersecting a portion of said principal thread, said first diameter being less than said second diameter[.];

said auxiliary thread having a first depth being less than a second depth of said principal thread by a factor of at least one-half.

18. (original) The molded closure of claim 17, wherein said auxiliary thread is helical.
19. (original) The molded closure of claim 17, wherein said side wall includes at least one tier.
20. (original) The molded closure of claim 19, wherein said side wall includes a first tier and a second tier, said first tier including said first inner wall of said cylindrical wall portion and said second tier including a second inner wall, said auxiliary thread being disposed on said first inner wall and said principal thread being disposed on said second inner wall.
21. (original) The molded closure of claim 17, wherein said auxiliary thread includes a first pitch and said principal thread includes a second pitch, said first pitch being unequal to said second pitch.
22. (original) A molded closure, comprising:

a primary helical thread formed on a cylindrical side wall of said molded closure;

---

a separate auxiliary thread formed on said cylindrical side wall of said molded closure along an upper periphery;

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

said primary helical thread having a first thread depth, said auxiliary thread having a second thread depth, said first thread depth being at least about double said second thread depth.

23. (currently amended) A molded closure having a primary thread and an auxiliary thread on an inner side wall, comprising:

a molded closure having an inwardly directed auxiliary helical thread and an inwardly directed primary helical thread, said auxiliary helical thread formed on a peripheral end of said molded closure, said auxiliary thread having a first thread depth, said primary thread having a second thread depth, said first thread depth less than said second thread depth by a factor of at least one-half;

said molded closure having a first and a second tier, said auxiliary thread formed on said first tier and said primary thread formed on said second tier;

wherein said auxiliary thread is a congruent helical thread and said primary thread is a congruent helical thread, said auxiliary thread incongruent with said primary thread.

24. (canceled)

25 (new) A molded closure which is easily removable from a mold core during manufacturing malfunctions, comprising:

a top wall;

~~a cylindrical side wall having an inner surface depending from said top wall;~~

an auxiliary thread having a first thread depth and being adjacent said top wall;

a primary thread having a second thread depth and being disposed at an end of said side

Appl. No.: 10/608,279  
Atty Docket: CG-851D  
Inventor: Francois

wall opposite said auxiliary thread;

said second thread depth being at least about twice said first thread depth;

said auxiliary thread and said primary thread extending from equivalent radial locations  
of said cylindrical side wall.

26 (new) A molded closure which is easily removable from a mold core during  
manufacturing malfunctions, comprising:

a top wall;

a substantially continuous cylindrical side wall having an inner surface depending from  
said top wall;

an auxiliary thread having a first thread depth and being adjacent said top wall;

a primary thread having a second thread depth and being disposed at an end of said side  
wall opposite said auxiliary thread;

said second thread depth being at least about twice said first thread depth;

said auxiliary thread and said primary thread extending from equivalent radial locations  
of said cylindrical side wall.